









# NHP and HEP Nylon Nozzle Holder

This high quality brand belongs to the product group "pressure blast systems". Only the perfect configuration and match of all system components in a blast machine enable maximum blasting efficiency. Therefore Clemco offers an extensive and complete range of quality products.



NHP and HEP Nylon Nozzle Holder Nozzle holder made of light but robust nylon, produced out of best raw materials. The combination of puristic design and long lifetime made our nozzle holders the standard in the abrasive market.

Blasting pressure	0 < > 12 bar
Operating temperature	-15°C < > +50°C















### nylon nozzle holder with screws

item #description	size
93236DHEP-0 NOZZLE HOLDER FINE THREAD, 13 X 7,5 MM	for hose 13 x 7,5 mm fine thread - ¾"
99173DHEP-3/4" NOZZLE HOLDER 19 X 7	for hose 19 x 7 mm fine thread - 11/4"
07720DHEP-1 NOZZLE HOLDER FINE THREAD, 25 X 7	for hose 25 x 7 mm fine thread - 11/4"
07721DHEP-2 NOZZLE HOLDER FINE THREAD, 32 X 8	for hose 32 x 8 mm fine thread - 1¼"
07722DHEP-3 NOZZLE HOLDER FINE THREAD, 38 X 9	for hose 38 x 9 mm fine thread - 11/4"
90269DNHP-0 NOZZLE HOLDER FOR HOSE 13 X 7	for hose 13 x 7,5 mm coarse thread 25 mm
99204DNHP-3/4" NOZZLE HOLDER FOR HOSE 19 X 7	for hose 19 x 7 mm coarse thread 50 mm
04106DNHP-1 NOZZLE HOLDER 25 X 7	for hose 25 x 7 mm coarse thread 50 mm
04127DNHP-2 NOZZLE HOLDER 32 X 8	for hose 32 x 8 mm coarse thread 50 mm
04128DNHP-3 NOZZLE HOLDER for HOSE 38 X 9	for hose 38 x 9 mm coarse thread 50 mm
07719DCFP-50 NOZZLE HOLDER	coupling / nozzle holder 50 mm





**Description** 

Fiber-reinforced nylon nozzle holder for abrasive blasting — with Contractor threads.

# NHP Nylon Nozzle Holders

Stock No. NHP-3/4 11398, NHP-1 04106, NHP-2 04127, NHP-3 04128



Note: For safe, efficient blasting, read and follow the owner's manual and seek training for everyone who will use this equipment.

## **Purpose**

The Clemco fiber-reinforced nylon nozzle holder attaches to the end of a blast hose and holds a contractor-thread blast

## **Description of Operation**NHP shown with optional

nozzle and hose

The blast hose must be cut squarely and cleanly. The nozzle holder is installed with the screws provided. These screws penetrate the outer wall, but not the inner wall of the blast hose.

In operation, the air pressure inside the blast hose helps hold the nozzle holder securely in place.

A nozzle washer must be placed on the *Nozzle must be* shoulder inside the nozzle holder to *ordered separately* prevent premature wear and failure, of

both the holder and the nozzle, from Advantages Related Clemco Literature high-speed abrasive.

• Fiber-reinforced nylon material springs **Description Stock No.** back from most impacts that would Contractor Series Catalog ......21385

Blast Hose dent or deform metal nozzle holders Abrasive Blasting Safety Practices......22090

• NHP-3/4fits Clemco 3/4 inch ID• Lighter weight than metal nozzle Blast Off 2 ......09294

• Precision dimensions

- NHP-1 fits Clemco 3/4 inch ID 2-braid Large thread makes changing nozzle hose and 1-inch ID Supa hose easy
- NHP-2fits Clemco 1 inch ID 2-braid

and 4-ply blast hose and 1-1/4 inch ID **Packaging** Supa hoseShips loose

• NHP-3 fits Clemco 1-1/4 inch IDModel Stock No. Dimensions Wt. 2-braid and 4-ply blast hose NHP-3/4 11398 2-1/4" x 3-15/16".5 lb

NozzlesNHP-1 04106 2-1/4" x 4" .5 lbAuthorized Distributor:

• Nozzle holders NHP-2 and NHP-3 NHP-2 04127 2-7/16" x 5-1/8".5 lb accept any contractor-thread nozzleNHP-3 04128 2-1/4" x 5-1/8" .5 lb

#### Color

Yellow



 $ISO\ 9001: 2008\ certified.\ Clemco\ is\ committed\ to\ continuous\ product\ improvement.\ Specifications\ are\ subject\ to\ change\ without\ notice.$